




OWS-S-200CD – RED

200cd Solar Obstruction Light Red

200cd Obstacle light for nighttime marking of structures that present a hazard to aviation. Steady-burning red visible light.

Solar skid that provides autonomous off-grid operation.



Key Features

- Two years warranty
- Compact and Lightweight
- CAA-UK CAP 437 compliant
- Built-in photocell
- Coated Stainless Steel skid structure
- 100.000 hours design life
- Easy to install

Performance characteristics

- 150 hours (12 nights) autonomous operation
- Horizontal beam pattern: 360°
- Steady burning
- Effective intensity: 200cd red
- Vertical beam pattern: 3° FWHM

Electrical characteristics

- Operating voltage: 12Vdc
- Battery capacity: 35Ah
- Battery type: AGM Battery
- Solar Panel: 110 Watt/peak Monocrystalline
- System power consumption: 3,2 Watt

Physical characteristics

- System dimensions: L x W x H: 1200x661x371 mm
- Mounting position: see drawing, next page
- Mounting: 4x Ø12 (M10x50> /excluded)
- Weight: 32,1 kg
- Gross Weight: 49 kg
- Design degree of protection: IP65
- Skid material: SS304, powder coated (SS316 optional)
- Operating temperature range: -20 °C/+50 °C




Offshore Warning Systems B.V.

Waldammeweg 7D, 4338 PM, Middelburg, The Netherlands.

KVK: 86564234 | VAT: NL864007577B01

www.offshorewarningsystems.com | tel: +31 6 53316982 | mail: info@owsbv.com



Order codes

Configuration table

ORDER CODE	LIGHT PERFORMANCE		
	DAY	TWILIGHT	NIGHT
OWS-S-200CD	OFF	OFF	200cd steady Red



Offshore Warning Systems B.V.

Waldammeweg 7D, 4338 PM, Middelburg, The Netherlands.


KVK: 86564234 | VAT: NL864007577B01

www.offshorewarningsystems.com | tel: +31 6 53316982 | mail: info@owsbv.com



DRAWING

General dimensions



Offshore Warning Systems B.V.

Waldammeweg 7D, 4338 PM, Middelburg, The Netherlands.

KVK: 86564234 | VAT: NL864007577B01

www.offshorewarningsystems.com | tel: +31 6 53316982 | mail: info@owsbv.com



Solar behavior

Calculated for The Netherlands

Provided information is based on the solar panel placement in optimal position towards the south. The data is based on Photovoltaic geographical information system at the European commission. The test location is The Netherlands. Data used are worst case numbers.

PVGIS-5 estimates of solar electricity generation

Provided inputs


Latitude/Longitude: 51.494,3.625
Horizon: Calculated
Database used: PVGIS-SARAH2
PV installed: 110 Wp
Battery capacity: 674.4 Wh

Slope angle: 30 °
Azimuth angle 0 °
Cutoff limit: 40 %
Consumption per day: 35 Wh (17,5 hours of operation)

Simulation outputs

Percentage days with full battery: 91.19 % Average energy not captured: 252.3 Wh
Percentage days with empty battery: 0 % Average energy missing: 13.92 Wh

Battery performance for off-grid PV system



Offshore Warning Systems B.V.

Waldammeweg 7D, 4338 PM, Middelburg, The Netherlands.
KVK: 86564234 | VAT: NL864007577B01
www.offshorewarningsystems.com | tel: +31 6 53316982 | mail: info@owsbv.com